NEW

ROTOMAX 3,5

The star of Grinding Machines

ROTOMAX STM 3,5 kW

Order Nr. 110 204
(400 V, 50 Hz, 3 Ph) 70 kg

- Variable speed button control selector.
- Speed gauge in LED display.
- Speed range with DIN 10 flexible shaft connection, 500 to 25000 rpm.
- Speed range with DIN 15 flexible shaft connection, 500 to 10000 rpm.
- Soft start, with built-in brake.
- Time saving due to simplified drive change.
- Dolly with tray for shafts and tools.

DIN 10

DIN 15

NA 4 x 1250 DIN10/G16 — Order Nr. 30 002 02 — G16

WB 4
Order Nr. 110 220

FH 4 (6 mm)
Order Nr. 57 570 01

WI 4 (3 mm)
Order Nr. 57 661 01

NA 7 x 1500 DIN10/G22 — Order Nr. 30 007 02 — G22

FH 7 (6 mm)
Order Nr. 49 530 01

WI 7 (6 mm)
Order Nr. 57 645 01

WIG 7
(M14) 2,7 : 1
max. 25 000 min^{-1}
Order Nr. 49 608 04

WB 7 (6 mm)
Order Nr. 110 221

NA 10 x 1500 DIN10/G28 — Order Nr. 30 026 02 — G28

NA 12 x 2000 DIN15/G28 — Order Nr. 30 030 02 — G28

NA 15 x 2000 DIN15/G35 — Order Nr. 30 032 02 — G35

BSG 15/63
Order Nr. 10 635 01

FH 10 (6 mm)
Order Nr. 57 170 01

WI 10 (6 mm)
Order Nr. 57 645 03

WB 10
Best.-Nr. 110 222

FH 12 (12 mm)
Order Nr. 48 265 01

for discs
∅ 178 mm,
max. 8000 rpm

FSM 2:1 (M14)
Order Nr. 57 891 06

BSG 10/50
Order Nr. 52 630 01

FH 15 (12 mm)
Order Nr. 10 331 01

WH 12 (MK1)
Order Nr. 10 330 01

WH 15 (MK2)
Order Nr. 10 340 01

SAM 1:1 (M14)
Order Nr. 10 443 01